A/M

t s19/3,ic,ba/all

19/3,IC,BA/1
DIALOG(R)File 351:Derwent WPI

014966664
WPI Acc No: 2003-027178/200302
  System and method for inputting **bar** **code** data in **electronic**
  apparatus
Patent Assignee: SAMSUNG ELECTRONICS CO LTD (SMSU)
Inventor: KIM E S
Number of Countries: 001 Number of Patents: 001
Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week	
KR 2002053652	A	20020705	KR 200083361	A	20001227	200302	B

Priority Applications (No Type Date): KR 200083361 A 20001227
Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
KR 2002053652	A		1	G06K-007/10	

Abstract (Basic): KR 2002053652 A
Abstract (Basic):
      NOVELTY - An **electronic** device **bar** **code** data inputting
  system and method is provided to transmit **bar** **code** data, read
  the data by a **bar** **code** reader, to a **wireless** module and to
  enable a **wireless** receiver of an **electronic** apparatus to
  receive and store the **bar** **code** data.
      DETAILED DESCRIPTION - The system comprises a **bar** **code**
  reader(1), a **wireless** transmitter(7), a bard code data transmission
  controller(3), a **bar** **code** data **storage** device(13) and an
  apparatus controller(11). The **bar** **code** reader(1) **reads** the
  bar **code** data from a **bar** **code** **label** adhered to an
  electronic apparatus. The **bar** **code** data transmission
  controller(3) converts the read **bar** **code** data into the data
  which the **wireless** transmitter(7) can process by adding
  identification data and a stop bit to the **bar** **code** data,
  and transmits the converted data to the **wireless** receiver via the
  wireless transmitter(7). The **wireless** transmitter(7) transmits
  the **bar** **code** data to the **wireless** receiver. The **bar**
  code data **storage** device(13) stores the transmitted data. The
  apparatus controller(11) stores the transmitted data at the **bar**
  code data **storage** device(13) according to a remote control
  signal transmitted via the **wireless** receiver. The apparatus
  controller(11) determines if the received data is **bar** **code**
  data, and stops storing the **bar** **code** data in the case that the
  stop bit is input.
      pp; 1 DwgNo 1/10
International Patent Class (Main): G06K-007/10

19/3,IC,BA/2
DIALOG(R)File 351:Derwent WPI

(R)